Test chamber investigation of the volatilization from source materials of brominated flame retardants and their subsequent deposition to indoor dust

Rauert, C.; Harrad, S.; Stranger, M.; Lazarov, B.

DOI:

[10.1111/ina.12151](https://doi.org/10.1111/ina.12151)

License:

None: All rights reserved

Document Version

Early version, also known as pre-print

Citation for published version (Harvard):

Rauert, C, Harrad, S, Stranger, M & Lazarov, B 2015, 'Test chamber investigation of the volatilization from source materials of brominated flame retardants and their subsequent deposition to indoor dust', *Indoor Air*, vol. 25, no. 4, pp. 393-404. <https://doi.org/10.1111/ina.12151>

[Link to publication on Research at Birmingham portal](#)

Publisher Rights Statement:

Eligibility for repository: Checked on 23/09/2015

General rights

Unless a licence is specified above, all rights (including copyright and moral rights) in this document are retained by the authors and/or the copyright holders. The express permission of the copyright holder must be obtained for any use of this material other than for purposes permitted by law.

- Users may freely distribute the URL that is used to identify this publication.
- Users may download and/or print one copy of the publication from the University of Birmingham research portal for the purpose of private study or non-commercial research.
- User may use extracts from the document in line with the concept of 'fair dealing' under the Copyright, Designs and Patents Act 1988 (?)
- Users may not further distribute the material nor use it for the purposes of commercial gain.

Where a licence is displayed above, please note the terms and conditions of the licence govern your use of this document.

When citing, please reference the published version.

Take down policy

While the University of Birmingham exercises care and attention in making items available there are rare occasions when an item has been uploaded in error or has been deemed to be commercially or otherwise sensitive.

If you believe that this is the case for this document, please contact UBIRA@lists.bham.ac.uk providing details and we will remove access to the work immediately and investigate.

Test chamber investigation of the volatilization from source materials of brominated flame retardants and their subsequent deposition to indoor dust

Rauert, Cassandra; Harrad, Stuart; Stranger, M.; Lazarov, B.

DOI:

[10.1111/ina.12151](https://doi.org/10.1111/ina.12151)

Citation for published version (Harvard):

Rauert, C, Harrad, S, Stranger, M & Lazarov, B 2015, 'Test chamber investigation of the volatilization from source materials of brominated flame retardants and their subsequent deposition to indoor dust' *Indoor Air*, vol 25, no. 4, pp. 393-404., 10.1111/ina.12151

[Link to publication on Research at Birmingham portal](#)

General rights

When referring to this publication, please cite the published version. Copyright and associated moral rights for publications accessible in the public portal are retained by the authors and/or other copyright owners. It is a condition of accessing this publication that users abide by the legal requirements associated with these rights.

- You may freely distribute the URL that is used to identify this publication.
- Users may download and print one copy of the publication from the public portal for the purpose of private study or non-commercial research.
- If a Creative Commons licence is associated with this publication, please consult the terms and conditions cited therein.
- Unless otherwise stated, you may not further distribute the material nor use it for the purposes of commercial gain.

Take down policy

If you believe that this document infringes copyright please contact UBIRA@lists.bham.ac.uk providing details and we will remove access to the work immediately and investigate.

1 **Research Highlights**

2
3
4
5
6
7
8

- Uptake of BFRs by dust following volatilisation from a source shown experimentally
- Migration of HBCDs from curtains elevated concentrations in dust up to 10 fold
- Test chamber design and sink effects are important considerations

1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65

1 **TITLE**
2 Test Chamber Investigation of the Volatilisation from Source Materials of
3 Brominated Flame Retardants and their Subsequent Deposition to Indoor Dust
4
5 4
6
7 5 **Authors**
8
9 6 C. Rauert^a, S. Harrad^a, M. Stranger^b, B. Lazarov^b
10
11 7
12
13 8 **Affiliation**
14 9 ^a School of Geography Earth and Environmental Sciences, University of Birmingham,
15 10 Birmingham, B15 2TT, UK
16 11 ^b Environmental Risk and Health Unit, VITO, Boeretang 200, 2400 , Mol, Belgium
17
18 12
19
20
21 13 **Corresponding Author**
22 14 Cassandra Rauert
23 15 *Division of Environmental Health & Risk Management, Public Health Building,*
24 16 *School of Geography, Earth & Environmental Sciences,*
25 17 *University of Birmingham,*
26 18 *Birmingham, B15 2TT, UK*
27 19 *Tel +44 (0)121 414 5431*
28 20 *Fax +44 (0)121 414 3078*
29 21 *c.b.rauert@bham.ac.uk*

Abstract

Numerous studies have reported elevated concentrations of brominated flame retardants (BFRs) in dust from indoor microenvironments. Limited information is available however on the pathways via which BFRs in source materials transfer to indoor dust. The most likely pathways hypothesised are: (a) volatilisation from the source with subsequent partitioning to dust, and (b) abrasion from everyday ‘wear and tear’ of the treated product that transfers microscopic fibres or particles to the dust. Test chambers are one method for investigating these pathways. This study reports on the development and application of an in-house test chamber for investigating BFR volatilisation from source materials and subsequent partitioning to dust. The performance of the chamber for such experiments was evaluated against that of a commercially available chamber, and inherent issues with such chambers were investigated, such as irreversible loss of BFRs to chamber surfaces (so-called “sink effects”). A sample of curtain fabric treated with hexabromocyclododecane (HBCD) was placed on a metal grid 10 cm above the chamber floor and subjected to emission testing. Concentrations of HBCD in dust placed on the chamber floor measured after the emission test, exceeded substantially those detected in the dust before the experiment. These results provide the first experimental evidence of HBCD volatilisation from a source material followed by deposition to dust.

Keywords

Brominated flame retardants, HBCDs, PBDEs, test chambers, transfer to dust, test chamber sink effects

1. Introduction

Brominated flame retardants (BFRs) are a class of chemicals used in numerous foam, material and plastic products in a variety of indoor microenvironments (Harrad et al., 2010). Often they are incorporated via an additive process, so are loosely bound to the polymer and available for release during normal use of the product. Alternatively, some BFRs are covalently bound to the polymer matrix, and referred to as “reactive” BFRs. Elevated concentrations of BFRs have been reported in indoor air and dust, with consequent implications for human exposure (Batterman et al., 2009; Harrad et al., 2008). Correlations have been reported between putative BFR sources and BFR concentrations in indoor air and dust in several studies (Allen et al., 2008; de Wit et al., 2012; Harrad et al., 2004); however, little is known about the pathways via which BFRs migrate from treated consumer products into air and dust. The principal pathways of migration or mass transfer from treated materials into dust are hypothesised to comprise: volatilisation with subsequent deposition (or partitioning) to dust, abrasion (‘wear and tear’) of the treated product leading to direct particle or fibre transfer to dust (Wagner et al., 2013; Webster et al., 2009), and migration via direct contact between source material and dust (Takigami et al., 2008). Actual migration is likely to be a combination of these pathways, with the relative significance of each, dependent on factors such as the physicochemical properties of the BFR and the mode via which it is incorporated into the product. For example, while abrasion is likely a viable pathway for both additive and reactive BFRs; the other two pathways are likely far less facile for reactive BFRs. The use of test chambers is a potentially important strategy for investigating migration pathways of FRs to dust.

Emission chambers have been utilised in studies for measurement of specific emission rates (SERs) of BFRs and organophosphorus flame retardants from consumer products, providing information on gas phase emissions (Rauert et al., 2014). In contrast, to the authors’ knowledge the migration of BFRs to particulates and dust has not been investigated via emission chambers; however the mass transfer of phthalates, another class of semi-volatile organic compound (SVOC), from wall paint and vinyl flooring to dust has been investigated in modified chambers (Clausen et al., 2004; Schripp et al., 2010). These studies demonstrated the migration of phthalates to dust

occurred via both volatilisation with subsequent deposition, and via direct transfer as a result of contact between the source material and dust.

The current study investigates the migration into dust *via* volatilisation and subsequent deposition of polybrominated diphenyl ethers (PBDEs) and hexabromocyclododecanes (HBCDs). An in-house test chamber was designed and built at the University of Birmingham. Experiments to evaluate the optimum configuration of this chamber are described, alongside its validation against a commercially available micro-emission chamber. Following validation, the in-house chamber was used to study the transfer of HBCDs from treated curtains into dust.

2. Materials and Methods

2.1 Test chamber apparatus

A cylindrical in-house designed and built test chamber was utilised at the University of Birmingham (UoB chamber), constructed from stainless steel with dimensions of 10 cm diameter and 20 cm height to give a total chamber volume of 1570 cm³, and internal surface area of 785 cm². Attachment of a Capex L2 Diaphragm Pump (Charles Austen Pumps Ltd, Surrey, UK) provided a constant air flow of 10 L min⁻¹ through the chamber, that led to an air change rate of 400 times per hour. Polyurethane foam (PUF) plugs (140 mm diameter, 12 mm thickness, 360.6 cm² surface area, 0.07 g cm⁻³ density, PACS, Leicester, UK) were attached to the exit air vent to collect analyte emissions in both the gas and airborne particulate phases. The chamber was maintained at the desired temperature by immersion in a hot water bath with chamber internal temperature monitored using a LogTag TRIX-8 temperature data logger (LoggerShop Technology, Dorset, UK). The chamber configuration is illustrated in Figure 1. Note the inclusion of an aluminium mesh shelf situated approximately halfway down the chamber. As detailed later, this permitted separation of a BFR source from dust placed on the chamber floor.

2.2 Commercially-available micro-chamber

A Micro-Chamber/Thermal ExtractorTM (Markes International) located at VITO (Flemish Institute for Technological Research), Belgium consisting of 6 linked chambers (Figure 2) was used for comparison with the UoB chamber. Each linked chamber, internal surfaces constructed of electropolished stainless steel, had

113 dimensions of 4.5 cm diameter and 2.8 cm height to give a total chamber volume of
114 44 cm³, and internal surface area of 71 cm². A uniform heating system (20-120°C)
115 surrounded each chamber and adjustable airflow set at 0.5 L min⁻¹ (air change rate of
116 682 times per hour) was provided to the chambers. The addition of a PUF plug (140
117 mm diameter, 12 mm thickness, 360.6 cm² surface area, 0.07 g cm⁻³ density, PACS,
118 Leicester, UK) to the exit air line, facilitated collection of emitted analytes. The
119 micro-chambers were also fitted with a shelf mid-way to facilitate separation of the
120 BFR source from dust.

122 *2.3 HBCD treated curtains and low level dust procurement*

123 Fabric curtains treated with the HBCD technical formulation were obtained from the
124 National Institute for Environmental Studies (NIES), Tsukuba, Japan. Concentrations
125 of HBCDs in these curtains were 18,000 mg kg⁻¹ for α -HBCD, 7,500 mg kg⁻¹ for β -
126 HBCD, and 17,000 mg kg⁻¹ for γ -HBCD (Kajiwara et al., 2013).

128 Initial source-air-dust partitioning experiments were conducted using a bulk house
129 dust sample obtained from a private residence in Birmingham. In common with many
130 UK dust samples, this dust contained moderately elevated concentrations of HBCDs
131 and of BDE-209, rendering it unsuitable for experiments studying these analytes. As a
132 result, a further bulk dust sample containing lower concentrations of PBDEs and
133 HBCDs was collected from a private residence in Belgium. Concentrations of PBDEs
134 and HBCDs in both dusts are provided as supplementary data (Table SD-1).

136 *2.4 Chemicals*

137 All solvents used for extraction and analysis were of HPLC grade quality (Fisher
138 Scientific, Loughborough, UK). Standards of individual PBDEs (BDEs 47, 85, 99,
139 100, 153, 154, 183, 209), HBCDs (α -HBCD, β -HBCD, γ -HBCD), labelled ¹³C
140 HBCDs (α -, β -, γ -), d₁₈ γ -HBCD and labelled ¹³C PBDEs (BDEs 47, 99, 100, 153,
141 209) were purchased from Wellington Laboratories (Guelph, ON, Canada). Florisil
142 (60-100 mesh) and silica gel (60Å, 60-100 mesh) were obtained from Sigma Aldrich
143 (Dorset, UK) with concentrated sulfuric acid procured from Merck (Darmstadt,
144 Germany). Large glass fibre filters (GFF, 12.5 cm diameter, 1 µm pore size, Whatman,
145 UK) and small GFFs (4.25 cm diameter, 0.7 µm pore size, Whatman, UK) were
146 purchased from Agilent (UK).

147

148 2.5 *Experimental Design for investigating BFR partitioning to dust after* 149 *volatilisation*

150 The chamber configuration for these experiments is illustrated in Figure 1b. It consists
151 of a known mass of pre-characterised dust (200 mg) weighed onto a GFF and placed
152 on the chamber floor. A piece of material known to contain BFRs (e.g. HBCD-treated
153 curtain) was placed on the mesh shelf located half way down the chamber. Post
154 experiment, the chamber was cooled at room temperature for 5 hours (with air flow
155 still attached) to minimise loss of volatiles when opening the chamber. The dust,
156 PUFs and GFFs were then extracted and analysed separately. All chamber inner wall
157 surfaces were washed with 200 mL of hexane:dichloromethane (1:1 v/v) and collected
158 for separate analysis.

159

160 2.6 *Analytical protocols*

161 2.6.1 *Sample preparation and extraction*

162 Sample extraction and purification was performed using slight modifications of in-
163 house published methods (Abdallah et al., 2009; Abdallah et al., 2008). Dust, PUFs
164 and GFFs were extracted with pressurised liquid extraction (ASE-350, Dionex Europe,
165 UK). PUFs and GFFs were packed into precleaned 66 mL cells using precleaned
166 Hydromatrix (Varian Inc., UK) to fill the void. Dust samples were loaded into pre-
167 cleaned 66 mL cells containing 1.5 g of pre-cleaned Florisil and Hydromatrix. Each
168 cell was spiked with 4 ng each of ¹³C-labelled α-, β-, and γ-HBCD; 40 ng of ¹³C-
169 PBDE 47; 10 ng each of ¹³C-labelled PBDE-99 and PBDE-153; and 20 ng of ¹³C-
170 PBDE 209 as internal (surrogate) standards prior to extraction with
171 hexane:dichloromethane (1:1 v/v) at 90 °C and 1500 psi. The cell was heated for 5
172 min, held static for 4 min and purged for 90 s, with a flush volume of 50%, for 3
173 cycles.

174

175 2.6.2 *Clean up*

176 The ASE extracts and chamber inner surface solvent rinses were combined and
177 concentrated to 0.5 mL using a Zymark Turbovap II (Hopkinton, MA, USA), then
178 purified by loading onto SPE cartridges filled with 8 g of pre-cleaned acidified silica
179 (44% concentrated sulfuric acid, w/w). The analytes were eluted with 30 mL of
180 hexane:dichloromethane (1:1, v/v), with the eluate evaporated to dryness under a

gentle stream of nitrogen. Samples were reconstituted to 100 μ L with 2 ng of d₁₈- γ -HBCD and 20 ng of ¹³C-PBDE 100 in HPLC grade methanol, used as recovery standards for internal standard recovery determination.

2.6.3 LC-MS/MS analysis

Target PBDEs and HBCDs were separated and analysed using modified, in-house published methods (Abdallah et al., 2009; Abdallah et al., 2008), using a dual pump Shimadzu LC-20AB Prominence liquid chromatograph (Shimadzu, Kyoto, Japan) equipped with a SIL-20A autosampler, and a DGU-20A3 vacuum degasser. Mass spectrometric analysis was performed using a Sciex API 2000 triple quadrupole mass spectrometer (Applied Biosystems, Foster City, CA) equipped with an APPI (PBDEs) or ESI (HBCDs) ion source, operated in negative ion mode.

2.6.3.1 PBDE Analysis

A Varian Pursuit XRS3 (Varian, Inc., Palo Alto, CA) C18 reversed phase analytical column (250 mm x 4.6 mm i.d., 3 μ m particle size) was used for separation of target PBDEs (47, 85, 99, 100, 153, 154, 183 and 209). A mobile phase programme based upon (mobile phase A) 1:1 methanol/water and (mobile phase B) 1:4 toluene/methanol at a flow rate of 0.4 mL min⁻¹ was applied for elution of the target compounds; starting at 85% (mobile phase B), increased linearly to 100% (mobile phase B) over 20 min, and then held for 10 min. The column was equilibrated with 85% (mobile phase B) for 5 min between runs. MS/MS detection, operated in MRM mode, was used for quantitative determination of the PBDE congeners based on m/z 420.8 $\rightarrow$ 78.8, m/z 500.8 $\rightarrow$ 78.8, m/z 578.8 $\rightarrow$ 78.8, m/z 658.6 $\rightarrow$ 78.8, m/z 486.6 $\rightarrow$ 78.8. ¹³C-labelled analogues were determined based on m/z 432.4 $\rightarrow$ 78.8, 512.4 $\rightarrow$ 78.8, 590.6 $\rightarrow$ 78.8, and m/z 494.7 $\rightarrow$ 78.8.

2.6.3.2 HBCD Analysis

A Varian Pursuit XRS3 C18 reversed phase analytical column (150 mm x 4.6 mm i.d., 3 μ m particle size) was used for separation of target HBCDs (α -, β -, γ -). A mobile phase program based upon (mobile phase A) 1:1 methanol/water and (mobile phase B) methanol at a flow rate of 0.18 mL min⁻¹ was applied for elution of the target compounds; starting at 50% (mobile phase B), then increased linearly to 100% (mobile phase B) over 4 min, held for 5 min before decreasing linearly to 88%

(mobile phase B) over 1 min. The column was equilibrated with 50% (mobile phase B) for 4 min between runs. MS/MS detection, operated in MRM mode, was used for quantitative determination of the HBCD diastereomers, ^{13}C -, and d_{18} -labelled analogues based on m/z 640.4 $\rightarrow$ 79.0, m/z 652.4 $\rightarrow$ 79.0, and m/z 657.7 $\rightarrow$ 79 respectively.

2.6.4 Quality Assurance

Samples were analysed using established QA/QC procedures. Method blanks were run with each batch of samples. For ^{13}C - α -, β -, and γ -HBCDs, average recoveries ranged from 64 to 97% while for ^{13}C -PBDE 47, 99, 153, and 209, average recoveries ranged between 69 and 80%. Accuracy and precision of the analytical method was assessed *via* replicate analyses ($n=7$) of NIST SRM 2585 (organics in house dust). The results of these analyses compared with indicative and certified values as appropriate are supplied as supplementary data (Table SD-2).

3. Results and Discussion

3.1 Experimental design development

3.1.1 Influence of exit air sampling train length

The influence of the length of polypropylene tubing carrying air exiting the chamber to the collection PUF was investigated in chamber experiments conducted at 60 °C for 24 hours, to promote volatilisation. In both experiments the BFR “source” was a small GFF (4.25 cm diameter) spiked with 100 ng of each of the target BFRs. Reducing the tubing length (pictured in Figure 1a) from 15 cm to 2 cm increased the mass of all BFRs collected on the PUFs by up to 7 times. Figure 3 and Table SD-3 compare the masses collected on the PUF for both tubing lengths – with results the average of 3 and 2 replicates for the 15 cm and 2 cm length tubing respectively. The substantially higher BFR masses detected on the PUF with shorter tubing length, suggests the analytes sorb strongly to the inner tubing surfaces thereby underestimating the extent of emissions via volatilisation. This is particularly relevant for chamber experiments conducted at above-ambient temperatures, which encourage volatilisation. Consistent with our data, Xu et al. (2012) reported that reducing the length of the stainless steel tube connecting their chamber to the sampling sorbent tube, increased apparent volatilisation of the phthalate DEHP from vinyl flooring. As a result of reducing the length of the connecting tube, Xu et al. (2012) found gas-phase concentrations

reached steady state conditions in 20 rather than 40 days. We conclude therefore that the length of the connection between the chamber exit and the sampling sorbent should be kept to a minimum for studies of SVOCs like BFRs.

3.1.2 PUF Breakthrough

To test the sampling efficiency of the PUFs used to collect BFRs in chamber exit air; two PUFs were placed sequentially in a glass holder with the chamber-side end of the first collection PUF spiked with standards of native PBDEs and HBCDs (100 ng/analyte) before attachment to the chamber. The empty chamber was maintained at 60 °C to replicate an experimental scenario in which substantial losses might be expected (warm air passing through the system configuration), and air was pumped through the system for 24 hours. Post experiment, both PUFs were extracted separately and analysed. Analyte concentrations were below LOQs on the second “air-side” PUF while recoveries of analytes on the chamber-side PUF were 99±7 %. These data are clear evidence that there is no significant analyte loss via PUF breakthrough with the UoB chamber. Similar experiments were conducted with the micro-chamber and also revealed satisfactory analyte recoveries of 90±11 %. Recoveries of individual analytes are listed in Table 1.

3.1.3 Sink Effects

The lower vapour pressure of SVOCs affects their study in test chambers as it can lead to preferential sorption, following their volatilisation, to chamber surfaces rather than collection in gas phase emissions. The loss of analytes via sorption to chamber wall surfaces is referred to as sink effects and has been previously reported in chamber studies of SVOCs (Katsumata et al., 2008; Kemmlein et al., 2003; Uhde and Salthammer, 2006; Xu et al., 2012). We investigated the loss to such sink effects in both the UoB test chamber and the micro-chamber configurations. To do so, GFFs spiked with standards of the analytes (100 ng/analyte) were placed inside the completely sealed off chambers (no air flow), which were then heated to 60 °C for 24 hours. Post experiment, whilst still sealed, both the UoB chamber and the micro-chamber were cooled to room temperature (22 °C) for 5 hours. The inner chamber surfaces were then rinsed as described in section 2.5 to assess the proportion of analytes reversibly deposited to such surfaces, and the GFF analysed to determine non-volatilised mass. Total mass recoveries of individual BFRs were then calculated

as the sum of masses detected in the chamber solvent rinses, and the GFF; with the mass unaccounted for assumed to be due to loss to irreversible sorption to internal chamber surfaces (i.e. “sink effects”).

Considerable levels of the more volatile analytes were recovered in the solvent washes of the chamber walls but 100% recovery was not obtained for any of the analytes. Table 2 lists the total % recovery of analytes in both the UoB and micro-chambers, with the proportions recovered from the chamber inner surface rinses and that remaining on the GFF reported separately. Liu et al. (2013) listed measures that can be undertaken to reduce such sink effects and minimise time for steady-state to be reached. These comprise: increasing the source surface area, decreasing the sink (i.e. chamber) surface area per volume ratio, using materials for chamber surfaces with lower sorptive capacity, and increasing the chamber air change rate. We therefore interpreted our data on loss to sink effects – which generally show a slightly greater loss for the micro-chamber - in this context.

As the same size GFF was used in both chambers and both chamber internal surfaces were stainless steel, no differences exist in the source area or the sorptive capacity of the internal surfaces of the two chambers. In contrast, the lower surface area-to-volume ratio for the UoB chamber ($0.5 \text{ m}^2.\text{m}^{-3}$) compared to the micro-chamber ($1.6 \text{ m}^2.\text{m}^{-3}$) should lead to a lower sink effects loss for the UoB chamber. However, this is offset to some extent by the lower air change rate for the UoB chamber (400 air changes per hour) compared to the micro-chamber (682 air changes per hour). The ratio of the differences between these two parameters for the two chambers suggests the loss to sink effects in the micro-chamber be about twice that of the UoB chamber. Our data are broadly consistent with this, suggesting that the factors listed by Liu et al (2013) are the principal parameters governing losses to sink effects and should be taken into account in future chamber design. However, the greater losses of BDE-209 in the UoB chamber highlights that other factors likely play a role.

Other efforts were made to minimise sink effects for the UoB chamber. We first explored the impact of the sorptive capacity of the internal chamber surface. To do so, experiments were repeated in a blown glass tube (20 cm length, 3 cm diameter) to compare sink effects using glass and stainless steel surfaces, and the impact of coating

the chamber interior with a Teflon spray to reduce active sorption sites was also evaluated. Improvements in analyte recovery were not observed using either glass or Teflon coated surfaces. In an attempt to reverse any sorption to chamber walls, the chamber was also heated post experiment to 80 °C for 6 hours, to volatilise analytes sorbed to chamber surfaces, but this yielded only minor improvements in analyte recovery from the chamber (an increase of 2-22%, see Table SD-4), and left up to 60% of analyte mass still unaccounted for. Higher post-experiment temperatures were avoided to prevent analyte degradation or thermal stereoisomerisation of HBCDs (Heeb et al., 2008).

To ascertain the full extent of sink effects from the stainless steel surfaces of the chamber, longer experiments of the order of months are required for attainment of steady state conditions inside the chamber, due to the slow emission rates and strong partitioning to chamber surfaces associated with SVOCs like BFRs (Xu et al., 2012). If steady state conditions are not reached then gas phase emissions and the rate of partitioning to dust may be underestimated. Our investigations suggest the UoB chamber is not constructed of low sorptive material and that over the experimental durations employed in this study, it is likely that steady state conditions are not attained. Therefore, our results are presented as an indicator of the importance of sink effects when determining SERs of BFRs and studying their migration to dust, and of the factors influencing sink effects; rather than a detailed study of partitioning to chamber interior surfaces.

3.2 Partitioning of BFRs to dust using standards spiked on a GFF as the source

Initial experiments evaluating the partitioning of BFRs to dust following their emission to air were conducted in both the UoB and the micro-chamber. In these experiments, a known mass of house dust (100-200 mg) was placed on a GFF on the chamber floor. Another GFF was spiked with standards of the analytes and placed on the wire mesh shelf, separated from the dust (by 5 cm in the UoB chamber and 1 cm in the micro-chamber), as the BFR ‘source’. To mimic operating conditions of electronic devices like PCs (Kemmler et al., 2003), the chamber was operated at 60 °C for 24 hours; with the dust, spiked GFF and chamber surface rinses analysed separately post-experiment. BFR partitioning to dust was observed in both chambers and Figure 4 shows the post-experiment increase in PBDE concentrations in the dust.

Data for the HBCDs and BDE-209 is not included as the UK house dust used in these initial experiments contained substantial concentrations of these analytes pre-experiment. The incremental concentration detected post-experiment in the dust is greater in the UoB chamber, likely due to the lower air change rate resulting in increased contact time compared to the micro-chamber. Conversely, as depicted in Figure 5, in the micro-chamber a greater proportion of the target analytes appear on the PUF with a lower proportion remaining on the GFF. Figure 5 also shows the proportion of the BFRs initially present in the “source” that is recovered in the various components of each experiment including the solvent chamber interior surface rinse. The micro-chamber was again more efficient at promoting volatilisation of BFRs which were subsequently collected on the PUF, rather than partitioning to dust, due to the micro-chamber’s comparatively higher air change rate (60% higher) and smaller volume. These result in a shorter distance between the “source” and air outlet leading to greater capture by the PUF. Note in Figures 4 and 5, the UoB chamber results are the average of 3 replicates and the micro-chamber data represent an average of 6 replicates.

3.3 Partitioning of HBCDs to dust using a HBCD treated curtain as the source

Following our initial experiments using spiked GFFs as the BFR “source”, partitioning to dust was investigated as previously using a 2 x 2 cm square piece of HBCD treated curtain placed on the chamber shelf as the source. The curtains were not obtained ‘new’ from the manufacturer having been stored at -18 °C for 2-3 years prior to testing. This is relevant as other studies have reported that the age of the product tested can influence emissions of SVOCs, with emissions significantly reducing over time (Carlsson et al., 2000; Ni et al., 2007; Salthammer et al., 2003). Thus emissions from this small sub-sample may not be representative of this and similar materials generally.

Initial experiments with the treated curtains were conducted in the UoB chamber for 24 hours at 60 °C to promote volatilisation of the analytes (n=4). Further experiments (n=3) in this chamber were conducted at room temperature for 1 week, to better simulate ‘real-world’ conditions. The average increment in concentrations of HBCDs in dust under both scenarios (at 60 °C and room temperature) is depicted in Figure 6. Similarly substantial increases in HBCD concentrations in dust were observed at the

end of both experiments, providing clear evidence of HBCD migration from the curtain to dust *via* volatilisation and subsequent partitioning.

Figure 6 also shows the pre- and post-experiment concentrations of HBCDs in dust when the 24 hour 60 °C experiments were conducted in the micro-chamber, using a sample of the same HBCD-treated curtain (n=6). Far greater variation in post-experiment concentrations was observed than those obtained under the same conditions using the UoB chamber. We believe this is because the source shelf in the micro-chamber placed the curtain only a very short distance (1 cm) from the entering airflow. Also the air change rate in the micro-chamber is 60% higher, resulting in a higher air velocity than in the UoB chamber. The resulting greater airflow turbulence, to which the curtain sample was exposed in the micro-chamber, caused abrasion of the curtain and the detection post-experiment of visible small fibres in the dust. Such abrasion was not reproducible and likely accounts for the more variable concentrations of HBCDs in the post-experiment dust samples. The importance of an appropriate experimental configuration is clearly shown by these results and the UoB chamber was more fit-for-purpose for these highly specific experiments.

4. Conclusions

Migration of HBCDs and PBDEs from source materials to dust *via* volatilisation and subsequent deposition was demonstrated for the first time in test chamber experiments, confirming that this pathway is an important contributor to the concentrations of BFRs widely observed in indoor dust. Experimental evidence is provided that confirms sink effects are an important issue associated with chamber studies of BFRs. Moreover, this study demonstrates that chamber configuration, dimensions, and operating conditions exert substantial influences on experimental outcomes, and that a thorough understanding of such factors is essential to facilitate correct interpretation of data generated by chamber studies. Notwithstanding these issues, the ease with which volatilisation from a source followed by deposition to dust can be reproduced in test chambers, both underlines the validity of this migration pathway, and the potential for similar chamber experiments to study the migration to dust of BFRs and other SVOCs from a range of source materials *via* this and other hypothesised pathways.

417 **Acknowledgements**

418 The research leading to these results has received funding from the European Union
419 Seventh Framework Program (*FP7/2007-2013*) under grant agreement No 264600
420 (INFLAME project). We also thank Natusuko Kajiwara and Hidetaka Takigami for
421 supplying the HBCD-treated curtain samples.
422

References

- Abdallah, M.A.-E.; Harrad, S.; Covaci, A. Isotope Dilution Method for Determination of Polybrominated Diphenyl Ethers Using Liquid Chromatography Coupled to Negative Ionization Atmospheric Pressure Photoionization Tandem Mass Spectrometry: Validation and Application to House Dust. *Analytical Chemistry*. 81:7460-7467; 2009
- Abdallah, M.A.-E.; Ibarra, C.; Neels, H.; Harrad, S.; Covaci, A. Comparative evaluation of liquid chromatography-mass spectrometry versus gas chromatography-mass spectrometry for the determination of hexabromocyclododecanes and their degradation products in indoor dust. *Journal of Chromatography A*. 1190:333-341; 2008
- Allen, J.G.; McClean, M.D.; Stapleton, H.M.; Webster, T.F. Linking PBDEs in House Dust to Consumer Products using X-ray Fluorescence. *Environmental Science & Technology*. 42:4222-4228; 2008
- Batterman, S.A.; Chernyak, S.; Jia, C.; Godwin, C.; Charles, S. Concentrations and Emissions of Polybrominated Diphenyl Ethers from U.S. Houses and Garages. *Environmental Science & Technology*. 43:2693-2700; 2009
- Carlsson, H.; Nilsson, U.; Östman, C. Video Display Units: An Emission Source of the Contact Allergenic Flame Retardant Triphenyl Phosphate in the Indoor Environment. *Environmental Science & Technology*. 34:3885-3889; 2000
- Clausen, P.A.; Hansen, V.; Gunnarsen, L.; Afshari, A.; Wolkoff, P. Emission of Di-2-ethylhexyl Phthalate from PVC Flooring into Air and Uptake in Dust: Emission and Sorption Experiments in FLEC and CLIMPAQ. *Environmental Science & Technology*. 38:2531-2537; 2004
- de Wit, C.A.; Björklund, J.A.; Thuresson, K. Tri-decabrominated diphenyl ethers and hexabromocyclododecane in indoor air and dust from Stockholm microenvironments 2: Indoor sources and human exposure. *Environment International*. 39:141-147; 2012
- Harrad, S.; de Wit, C.A.; Abdallah, M.A.-E.; Bergh, C.; Björklund, J.A.; Covaci, A.; Darnerud, P.O.; de Boer, J.; Diamond, M.; Huber, S.; Leonards, P.; Mandalakis, M.; Östman, C.; Haug, L.S.; Thomsen, C.; Webster, T.F. Indoor Contamination with Hexabromocyclododecanes, Polybrominated Diphenyl

456 Ethers, and Perfluoroalkyl Compounds: An Important Exposure Pathway for
457 People? *Environmental Science & Technology*. 44:3221-3231; 2010
458 Harrad, S.; Ibarra, C.; Abdallah, M.A.-E.; Boon, R.; Neels, H.; Covaci, A.
459 Concentrations of brominated flame retardants in dust from United Kingdom
460 cars, homes, and offices: Causes of variability and implications for human
461 exposure. *Environment International*. 34:1170-1175; 2008
462 Harrad, S.; Wijesekera, R.; Hunter, S.; Halliwell, C.; Baker, R. Preliminary
463 Assessment of U.K. Human Dietary and Inhalation Exposure to
464 Polybrominated Diphenyl Ethers. *Environmental Science & Technology*.
465 38:2345-2350; 2004
466 Heeb, N.V.; Bernd Schweizer, W.; Mattrel, P.; Haag, R.; Gerecke, A.C.; Schmid, P.;
467 Zennegg, M.; Vonmont, H. Regio- and stereoselective isomerization of
468 hexabromocyclododecanes (HBCDs): Kinetics and mechanism of γ - to α -
469 HBCD isomerization. *Chemosphere*. 73:1201-1210; 2008
470 Kajiwara, N.; Desborough, J.; Harrad, S.; Takigami, H. Photolysis of brominated
471 flame retardants in textiles exposed to natural sunlight. *Environmental*
472 *Science: Processes & Impacts*. 15:653-660; 2013
473 Katsumata, H.; Murakami, S.; Kato, S.; Hoshino, K.; Ataka, Y. Measurement of semi-
474 volatile organic compounds emitted from various types of indoor materials by
475 thermal desorption test chamber method. *Building and Environment*. 43:378-
476 383; 2008
477 Keller, J.M.; Stapleton, H.M.; Heltsley, R.; Peck, A.; Kucklick, J.R.; Schantz, M.M.;
478 Wise, S.A. Standard reference materials available from the National Institute
479 of Standards and Technology for the analysis of brominated flame retardants.
480 Poster presented at BFR 2007; The Netherlands: Amsterdam. 2007
481 Kemmlein, S.; Hahn, O.; Jann, O. Emissions of organophosphate and brominated
482 flame retardants from selected consumer products and building materials.
483 *Atmospheric Environment*. 37:5485-5493; 2003
484 Liu, C.; Liu, Z.; Little, J.C.; Zhang, Y. Convenient, Rapid and Accurate Measurement
485 of SVOC Emission Characteristics in Experimental Chambers. *PLOS ONE*.
486 8:e72445; 2013
487 Ni, Y.; Kumagai, K.; Yanagisawa, Y. Measuring emissions of organophosphate flame
488 retardants using a passive flux sampler. *Atmospheric Environment*. 41:3235-
489 3240; 2007

490 Rauert, C.; Lazarov, B.; Harrad, S.; Covaci, A.; Stranger, M. A review of chamber
 491 experiments for determining specific emission rates and investigating
 492 migration pathways of flame retardants. *Atmospheric Environment*. 82:44-55;
 493 2014
 494 Salthammer, T.; Fuhrmann, F.; Uhde, E. Flame retardants in the indoor environment –
 495 Part II: release of VOCs (triethylphosphate and halogenated degradation
 496 products) from polyurethane. *Indoor Air*. 13:49-52; 2003
 497 Schripp, T.; Fauck, C.; Salthammer, T. Chamber studies on mass-transfer of di(2-
 498 ethylhexyl)phthalate (DEHP) and di-n-butylphthalate (DnBP) from emission
 499 sources into house dust. *Atmospheric Environment*. 44:2840-2845; 2010
 500 Stapleton, H.; Harner, T.; Shoeib, M.; Keller, J.; Schantz, M.; Leigh, S.; Wise, S.
 501 Determination of polybrominated diphenyl ethers in indoor dust standard
 502 reference materials. *Analytical and Bioanalytical Chemistry*. 384:791-800;
 503 2006
 504 Takigami, H.; Suzuki, G.; Hirai, Y.; Sakai, S.-i. Transfer of brominated flame
 505 retardants from components into dust inside television cabinets. *Chemosphere*.
 506 73:161-169; 2008
 507 Uhde, E.; Salthammer, T. Influence of molecular parameters on the sink effect in test
 508 chambers. *Indoor Air*. 16:158-165; 2006
 509 Wagner, J.; Ghosal, S.; Whitehead, T.; Metayer, C. Morphology, spatial distribution,
 510 and concentration of flame retardants in consumer products and environmental
 511 dusts using scanning electron microscopy and Raman micro-spectroscopy.
 512 *Environment International*. 59:16-26; 2013
 513 Webster, T.F.; Harrad, S.; Millette, J.R.; Holbrook, R.D.; Davis, J.M.; Stapleton,
 514 H.M.; Allen, J.G.; McClean, M.D.; Ibarra, C.; Abdallah, M.A.-E.; Covaci, A.
 515 Identifying Transfer Mechanisms and Sources of Decabromodiphenyl Ether
 516 (BDE 209) in Indoor Environments Using Environmental Forensic
 517 Microscopy. *Environmental Science & Technology*. 43:3067-3072; 2009
 518 Xu, Y.; Liu, Z.; Park, J.; Clausen, P.A.; Benning, J.L.; Little, J.C. Measuring and
 519 Predicting the Emission Rate of Phthalate Plasticizer from Vinyl Flooring in a
 520 Specially-Designed Chamber. *Environmental Science & Technology*.
 521 46:12534-12541; 2012
 522

Figures and Tables

Figure 1: (Top) Photograph of UoB test chamber configured for experiments monitoring emissions to air and (bottom) Schematic of experimental design for source-air-dust transfer experiments. For UoB chamber $x,y = 10\text{ cm}$, for micro-chamber $x = 1\text{ cm}$, $y = 2\text{ cm}$.

Figure 2: Photographs of the micro-chamber showing (top) Chamber modifications for the dust experiments, and (bottom) Experimental configuration of the 6 linked chambers configured for monitoring emissions to air.

Figure 3: Mass of BFR (ng) collected on PUF plugs sampling chamber exit air for different exit air sampling train lengths

Figure 4: Concentrations (ng g^{-1}) of PBDEs in dust, pre and post partitioning experiment in the UoB chamber ($n=3$) and micro-chamber ($n=6$) using a spiked GFF as the source

Figure 5: Average recovery (%) of PBDEs in various components in (top) the UoB chamber (n=3) and (bottom) the micro-chamber (n=6) using a spiked GFF as the source

Figure 6: Concentrations of HBCDs in dust (ng g^{-1}) pre- and post-experiments using a HBCD-treated curtain as the source after: (top) 24 hours at 60 °C in the UoB chamber ($n=4$); (middle) 1 week at room temperature in the UoB chamber ($n=3$), and (bottom) 24 hours at 60 °C in the micro-chamber ($n=6$)

Table 1: Recoveries (%) of BFRs from PUF breakthrough experiments

	BDE-47	BDE-85	BDE-99	BDE-100	BDE-153	BDE-154	BDE-183	BDE-209	α -HBCD	β -HBCD	γ -HBCD
<i>Birmingham Chamber</i>	93	106	105	106	101	100	92	107	92	93	100
<i>Micro-chamber</i>	102	80	94	92	88	89	82	92	82	87	83

Table 2: Average ($\pm$ standard deviation) recoveries of PBDEs and HBCDs from various components during experiments testing sink effects for the UoB and micro-chambers

	BDE-47	BDE-85	BDE-99	BDE-100	BDE-153	BDE-154	BDE-183	BDE-209	α -HBCD	β -HBCD	γ -HBCD
<i>Total recovery (%) UoB chamber (n=1)</i>	43	52	54	51	89	78	76	90	89	70	65
<i>Total recovery (%) Micro-chamber (n=8)</i>	47 $\pm$ 14	50 $\pm$ 6.1	49 $\pm$ 8.9	46 $\pm$ 13	53 $\pm$ 9.1	51 $\pm$ 12	60 $\pm$ 6.0	97 $\pm$ 14	55 $\pm$ 22	36 $\pm$ 21	25 $\pm$ 26
<i>Recovery (%) GFF-UoB</i>	5.3	21	13	10	59	35	71	85	86	69	63
<i>Recovery (%) GFF - Micro</i>	6.2 $\pm$ 5.9	13 $\pm$ 6.0	10 $\pm$ 5.4	8.0 $\pm$ 5.2	25 $\pm$ 14	15 $\pm$ 13	45 $\pm$ 11	96 $\pm$ 14	45 $\pm$ 21	32 $\pm$ 20	20 $\pm$ 23
<i>Recovery (%) surface rinse - UoB</i>	38	32	41	41	30	43	5.6	4.3	2.6	1.0	1.8
<i>Recovery (%) surface rinse - Micro</i>	41 $\pm$ 9.8	37 $\pm$ 4.0	39 $\pm$ 5.5	38 $\pm$ 8.5	28 $\pm$ 5.7	36 $\pm$ 5.0	15 $\pm$ 5.3	1.4 $\pm$ 0.8	10 $\pm$ 3.1	4.4 $\pm$ 1.5	5.1 $\pm$ 2.9

Supplementary Data

Table SD-1: Average starting concentrations of BFRs (ng g⁻¹) in bulk dust used for chamber experiments from 6 and 7 repeat analyses respectively

	BDE-47	BDE-85	BDE-99	BDE-100	BDE-153	BDE-154	BDE-183	BDE-209	α -HBCD	β -HBCD	γ -HBCD
<i>Birmingham House Dust (n=6)</i>	4.6 ± 7.8	0.6 ± 1.0	17 ± 4.1	4.1 ± 1.6	6.6 ± 4.6	2.5 ± 4.9	11 ± 6.7	2036 ± 551	393 ± 106	180 ± 45	2609 ± 3238
<i>Belgian House Dust (n=7)</i>	9.9 ± 11	2.0 ± 1.8	27 ± 31	4.6 ± 4.7	5.9 ± 6.1	3.1 ± 3.0	1.9 ± 2.1	230 ± 176	46 ± 19	13 ± 10	50 ± 39

Table SD-2: Average concentrations (ng g⁻¹) in 7 analyses of SRM 2585 and the reported certified PBDE (Stapleton et al., 2006) and indicative HBCD values (Keller et al., 2007)

	BDE-47	BDE-85	BDE-99	BDE-100	BDE-153	BDE-154	BDE-183	BDE-209	α -HBCD	β -HBCD	γ -HBCD
<i>SRM Measured Value (n=7)</i>	347 ± 39	35.1 ± 4.6	730 ± 93	133 ± 13	126 ± 13	78.6 ± 13	44.4 ± 5.0	2460 ± 400	19 ± 5.7	5.6 ± 2.2	98 ± 35
<i>Certified/Indicative Values</i>	498 ± 46	43.8 ± 1.6	892 ± 53	145 ± 11	119 ± 11	83.5 ± 2.0	43.0 ± 3.5	2510 ± 190	19 ± 3.7	4.3 ± 1.1	120 ± 22

Table SD-3: BFR mass collected on PUFs with different air sampling train lengths and analytes recovered (%) by heating the chamber post experiment

	BDE-47	BDE-85	BDE-99	BDE-100	BDE-153	BDE-154	BDE-183	BDE-209	α -HBCD	β -HBCD	γ -HBCD
<i>PUF mass (ng) 15 cm tubing (n=3)</i>	21 ± 16	2.8 ± 0.6	4.9 ± 1.9	8.4 ± 4.5	1.0 ± 0.3	2.3 ± 0.5	0.4 ± 0.1	3.2 ± 1.4	1.9 ± 0.2	0.7 ± 0.1	1.2 ± 0.4
<i>PUF mass (ng) 2 cm tubing (n=2)</i>	65 ± 23	15 ± 2.9	34 ± 2.6	51 ± 0.8	6.3 ± 1.0	16 ± 0.7	1.5 ± 0.2	8.4 ± 7.7	14 ± 0.1	5.9 ± 2.3	28 ± 7.7

Table SD-4: BFR recovery (%) on chamber exit PUF achieved by heating UoB chamber post-experiment to 80 °C for 6 hours

<i>Recovery (%) (n=3)</i>	2.1 ± 1.7	8.8 ± 4.7	9.0 ± 4.9	5.6 ± 3.3	4.5 ± 1.7	6.9 ± 3.5	1.7 ± 0.9	3.0 ± 1.0	12 ± 13	4.6 ± 6.3	22 ± 29
---------------------------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	-----------	---------	-----------	---------

Conflict of Interest Declaration

We wish to confirm that there are no known conflicts of interest associated with this publication and there has been no significant financial support for this work that could have influenced its outcome.

We confirm that the manuscript has been read and approved by all named authors and that there are no other persons who satisfied the criteria for authorship but are not listed. We further confirm that the order of authors listed in the manuscript has been approved by all of us.

We confirm that we have given due consideration to the protection of intellectual property associated with this work and that there are no impediments to publication, including the timing of publication, with respect to intellectual property. In so doing we confirm that we have followed the regulations of our institutions concerning intellectual property.

We understand that the Corresponding Author is the sole contact for the Editorial process (including Editorial Manager and direct communications with the office). He/she is responsible for communicating with the other authors about progress, submissions of revisions and final approval of proofs. We confirm that we have provided a current, correct email address which is accessible by the Corresponding Author and which has been configured to accept email from: c.b.rauert@bham.ac.uk

Signed by all authors as follows:

Cassandra Rauert

C. Rauert 13/3/14

Stuart Harrad

S. Harrad 13/3/14

Marianne Stranger

M. Stranger 14/03/2014

Borislav Lazarov

B. Lazarov 14/03/2014