

Radiofrequency exposure amongst employees of mobile network operators and broadcasters

Litchfield, Ian; Sorahan, Thomas; van Tongeren, Martie

DOI:

[10.1093/rpd/ncw283](https://doi.org/10.1093/rpd/ncw283)

License:

Creative Commons: Attribution (CC BY)

Document Version

Publisher's PDF, also known as Version of record

Citation for published version (Harvard):

Litchfield, I, Sorahan, T & van Tongeren, M 2016, 'Radiofrequency exposure amongst employees of mobile network operators and broadcasters', *Radiation Protection Dosimetry*. <https://doi.org/10.1093/rpd/ncw283>

[Link to publication on Research at Birmingham portal](#)

General rights

Unless a licence is specified above, all rights (including copyright and moral rights) in this document are retained by the authors and/or the copyright holders. The express permission of the copyright holder must be obtained for any use of this material other than for purposes permitted by law.

- Users may freely distribute the URL that is used to identify this publication.
- Users may download and/or print one copy of the publication from the University of Birmingham research portal for the purpose of private study or non-commercial research.
- User may use extracts from the document in line with the concept of 'fair dealing' under the Copyright, Designs and Patents Act 1988 (?)
- Users may not further distribute the material nor use it for the purposes of commercial gain.

Where a licence is displayed above, please note the terms and conditions of the licence govern your use of this document.

When citing, please reference the published version.

Take down policy

While the University of Birmingham exercises care and attention in making items available there are rare occasions when an item has been uploaded in error or has been deemed to be commercially or otherwise sensitive.

If you believe that this is the case for this document, please contact UBIRA@lists.bham.ac.uk providing details and we will remove access to the work immediately and investigate.

RADIOFREQUENCY EXPOSURE AMONGST EMPLOYEES OF MOBILE NETWORK OPERATORS AND BROADCASTERS

Ian Litchfield^{1,*}, Martie van Tongeren² and Tom Sorahan¹

¹Institute of Applied Health Research, College of Medical and Dental Sciences, University of Birmingham, Edgbaston, Birmingham B15 2TT, UK

²Institute of Occupational Medicine, Research Avenue North, Riccarton, Edinburgh EH14 4 AP, UK

*Corresponding author: I.Litchfield@bham.ac.uk

Little is known about personal exposure to radiofrequency (RF) fields amongst employees in the telecommunications industry responsible for installing and maintaining transmitters. IARC classified RF exposure as a possible carcinogen, although evidence from occupational studies was judged to be inadequate. Hence, there is a need for improved evidence of any potentially adverse health effects amongst the workforce occupationally exposed to RF radiation. In this study, results are presented from an exposure survey using data from personal monitors used by employees in the broadcasting and telecommunication industries of the UK. These data were supplemented by spot measurements using broadband survey metres and information on daily work activities provided by employee questionnaires. The sets of real-time personal data were categorised by four types of site determined by the highest powered antenna present (high, medium or low power and ground-level sites). For measurements gathered at each type of site, the root mean square and a series of box plots were produced. Results from the daily activities diaries suggested that riggers working for radio and television broadcasters were exposed to much longer periods as compared to colleagues working for mobile operators. Combining the results from the measurements and daily activity diaries clearly demonstrate that exposures were highest for riggers working for broadcasting sites. This study demonstrates that it is feasible to carry out exposure surveys within these populations that will provide reliable estimates of exposure that can be used for epidemiological studies of occupational groups exposed to RF fields.

INTRODUCTION

The growing prevalence of mobile phones and their associated infrastructure has brought concerns about adverse health effects^{1–6} to the forefront of public and political concern^{7–10}. Recently, IARC classified radiofrequency (RF) as a possible carcinogen based primarily on ‘limited’ evidence for an association of glioma and acoustic neuroma with mobile telephone use, although it described evidence in relation to the occupationally exposed as ‘inadequate’¹¹. Large scale studies continue to explore the association between RF exposure and adverse health effects¹². This is likely to generate renewed interest in the effects of RF on the human body. However the accurate monitoring of personal RF exposure remains a significant inhibitive factor, particularly in complex work environments that can contain a wide range of sources, powers and frequencies, a challenge that has been widely acknowledged¹³.

Some of the most powerful emitters of RF can be found in the telecommunications and broadcasting industries and therefore the exposure of the workers they employ is of particular interest. The nature of occupational exposure within these working environments is dependent upon the RF and power of the antennas they encounter, the physical characteristics of the environment where they are housed, and the regularity with which they are visited. As a result, and dependent upon their roles and responsibilities,

employees can experience exposures of varying duration and intensity.

Only a limited amount of research has been published on occupational RF exposures of workers in the telecommunication and broadcast industries^{14–16}. Though the combination continues to evolve, the types of RF source have been established for some time and here results are presented from a study that explored the exposure of telecommunication and broadcast employees in the UK in the early 2000 s¹⁴.

METHODS

Settings

This work involves those employed either by mobile network operators, or the broadcasting industry in the UK. The network operators provide the infrastructure to support services across the GSM networks using antennas located singly or with other antennas on a range of structures including towers, masts and roof-tops. These antennas can be sector or omnidirectional, operate at frequencies of 900 and 1800 MHz, and have individual powers of up to 10 W, which could add up to 70 W for heavily used sites. The broadcasters distribute audio and/or video signals via antennas that are commonly housed on purpose built structures. They use medium, high, very high-frequency (VHF) and ultra high-frequency

(UHF) systems ranging from 3 MHz up to 3.0 GHz and radiated power up to 200 kW.

Participants

Those employees whose exposure could potentially exceed International Commission on Non-ionising Radiation Protection (ICNIRP) reference levels for public exposure¹⁷ were invited to participate. Senior managers at each company helped identify the job titles of eligible staff. Those whose RF exposure was solely as a result of mobile phone usage or from using wireless local networks were excluded. Those eligible received an information leaflet containing information on the study and allowing them to provide informed consent.

Data collection

Data that were collected by I.L., and first analysed by Cooper *et al.*¹⁴ are presented. In collecting these data, two designs of personal monitors were used over the course of the study. The majority of measurements was made with the Wandel & Goltermann ESM-20, designed to measure field strengths and

then present them as a percentage of the ICNIRP¹⁷ reference levels. They were sensitive to electric fields 1 MHz to 40 GHz¹⁰. During the latter stages of the study, the Nardalert XT was used, which was both sensitive to a broader range of frequencies, i.e. 100 kHz to 100 GHz, and could measure electric field strength levels down to 10% of ICNIRP guidelines¹⁸ (see Table 1)¹⁷. Each data point is the average of 20 measurements taken over a 2 s period. The monitors were worn on the breast pocket of each participant and a member of the study team was present each time a monitor was worn to ensure this location was consistent for all participants. To further characterise the exposure regimes experienced by cohort, a series of spot measurements in the vicinity of telecommunication antennas and UHF and VHF broadcast antennas were also conducted using three different types of broadband survey metre; the Holaday HI-4417, and the Narda 8716 and 8712 survey metres.

To capture data on the typical length of exposure to RF for different groups of workers across both industries, questionnaires were distributed to employees in each company. These captured information on the typical activities during the working day including duration of working in areas with possible

Table 1. ICNIRP guidelines for exposure to time varying electric and magnetic fields for frequencies up to 10 GHz.

Exposure characteristics	Frequency range	Current density for head and trunk (mA m ⁻²) (rms)	Whole-body average SAR (W kg ⁻¹)	Localised SAR	
				(head and trunk) (W kg ⁻¹)	(limbs) (W kg ⁻¹)
Occupational exposure	Up to 1 Hz	40	—	—	—
	1–4 Hz	40/ <i>f</i>	—	—	—
	4 Hz–1 kHz	10	—	—	—
	1–100 kHz	<i>f</i> /100	—	—	—
	100 kHz–10 MHz	<i>f</i> /100	0.4	10	20
	10 MHz–10 GHz	—	0.4	10	20

Notes:

1. *f* is the frequency in Hz.
2. Because of electrical inhomogeneity of the body, current densities should be averaged over a cross-section of 1 cm² perpendicular to the current direction.
3. For frequencies up to 100 kHz, peak current density values can be obtained by multiplying the rms value by u_2 (1.414). For pulses of duration t_p the equivalent frequency to apply in the basic restrictions should be calculated as f_5 $1/(2t_p)$.
4. For frequencies up to 100 kHz and for pulsed magnetic fields, the maximum current density associated with the pulses can be calculated from the rise/fall times and the maximum rate of change of magnetic flux density. The induced current density can then be compared with the appropriate basic restriction.
5. All SAR values are to be averaged over any 6-min period.
6. Localised SAR averaging mass is any 10 g of contiguous tissue; the maximum SAR so obtained should be the value used for the estimation of exposure.
7. For pulses of duration t_p the equivalent frequency to apply in the basic restrictions should be calculated as f_5 $1/(2t_p)$. Additionally, for pulsed exposures in the frequency range 0.3–10 GHz and for localised exposure of the head, in order to limit or avoid auditory effects caused by thermoelastic expansion, an additional basic restriction is recommended. This is that the SA should not exceed 10 mJ kg⁻¹ for workers and 2 mJ kg⁻¹ for the general public, averaged over 10 g tissue.

RF exposure. Each individual received 10 questionnaires to account for two working weeks.

Analysis

The data recorded by personal monitors were collated by type of site visited and Uncensor 4.0¹⁹ software was used to produce measures of central tendency, and to carry out a root mean square (rms) analysis. Data on work activity from each company were collated and produced descriptive statistics of the amount of time spent working in proximity to RF emitters by sector and job type.

RESULTS

Telecommunication sites

A total of seven sites primarily used for telecommunications were visited and spot measurements undertaken. Additional radio systems were also located at some of these sites including omnidirectional paging antennas and point-to-point microwave links. The strongest ambient field strengths were found near pager antennas. The field strengths from dish antennas were commonly below the detection threshold of the instrumentation. The measurements are summarised in Table 2.

VHF/UHF broadcast sites

A total of seven sites were visited. The sites each hosted at least one or more of the following transmitters: analogue television, digital television, national FM radio, local FM radio and DAB. Also in place were

telecommunication systems including GSM base stations, wide-area paging and point-to-point microwave links.

Where UHF television transmitters were installed, signals were usually transmitted via arrays of antennas enclosed within weatherproof cylinders at the top of the structure. Measurements taken within the vicinity UHF antennas are summarised in Table 3. The VHF radio signals were transmitted via arrays of dipole antennas situated at the top of the tower and were generally arranged in three or four columns. The spot measurements taken in the vicinity of these antennas are summarised in Table 4.

Summary of exposure by site

Staff from seven companies participated: four mobile phone operators and three broadcasters, and a total of 124 completed exposure records were obtained. Here, measures of central tendency are presented as produced by the software program UnCensor 4.0¹⁹.

The novel treatment of the data produced a rms analysis. The rms and maximum electric field strength were calculated across four types of site defined by the most powerful antenna at that site. High-power sites are UHF or VHF broadcast sites where powers were in excess of 1 kW. Medium power sites are those with UHF or VHF transmitting powers in the range of 10–1000 W or sites with paging antennas. Low-power sites are those where the most powerful transmitters were associated with GSM base stations where transmitting powers are <10 W per channel. Ground-level sites are where employees worked only at ground level. These data are summarised in Figure 1 where rms exposures are denoted by vertical lines. RF levels

Table 2. Electric field strength measured in the vicinity of telecommunications antennas.

Location	Electric field strength (V m ⁻¹)						
	Site 1	Site 2	Site 3	Site 4	Site 5	Site 6	Site 7
Ambient level above platforms/roof top	1–20	8–50	10–40	≤17	3–5	4–12	<1–7
Near pager antenna	—	—	350	—	—	—	—
1–2 m laterally from pager antennas	—	50–75	—	—	—	—	—
Near horizontal boom for pager antenna	—	—	570	—	—	—	—
Near vertical support pole for pager antenna	—	—	60–90	—	—	—	50–90
1 m from vertical support pole for pager antenna	—	—	—	—	—	—	15–19
Beneath GSM sector antennas	20	—	—	—	—	≤11	—
Behind GSM sector antennas	24	—	—	—	≤8	≤11	≤12
Adjacent to GSM sector antennas	—	—	—	—	—	23	—
In front of GSM sector antennas	30	—	—	—	—	72	—
Behind microwave dish antennas	—	—	—	≤11	—	≤9	—
In front of microwave dish antennas	<6	—	75 ^a	—	—	—	—
Near unidentified VHF/UHF antennas	—	—	270	—	—	13	—
Near protective barrier around perimeter of roof	—	—	180	—	—	—	—

^aThe electric field strength measured at this location was likely to have been largely due to other nearby VHF/UHF antennas rather than the 1.2 m microwave dish.

Table 3. Electric field strength measured in the vicinity of UHF television antennas.

General location	Details	Electric field strength ($V m^{-1}$)		
		Site 2	Site 4	Site 5
In between two antenna arrays	Ambient level	—	—	60–100
Top platform, just beneath main analogue array (four channels)	Ambient level	40–90	10–20	—
	Close to steelwork	—	25	—
	Close to splitter	>270	—	—
Inside secondary analogue array (single channel)	Ambient level	—	40	—
	Close to ladder	—	60	—
	Close to feeders	—	90	—
Inside digital array	Ambient level ^a	—	20–30	—

^aNo localised field strengths materially exceeding the ambient level were found in this region.

Table 4. Electric field strength measured in the vicinity of VHF broadcast radio antennas.

General location	Details	Electric field strength ($V m^{-1}$)					
		Site 1	Site 2	Site 3	Site 4	Site 6	Site 7
Platform above main array (four channels)	Ambient level	50–	100	—	—	—	—
	Near splitter	100–	190	—	—	—	—
Platform beneath main array	Ambient level	30	60	—	20	—	—
	Near ladder	—	—	—	40–80	—	—
	Near feeders	—	—	—	200	—	—
	Near steelwork	—	—	—	300	—	—
Inside main array	Ambient level	120	150–250	—	—	—	20–
	Near ladder	270	—	—	—	—	25
	Near steelwork	390	—	—	—	—	—
	Close behind antennas	240	480	—	—	—	30
	Near splitter	450	—	—	—	—	—
Adjacent to local FM radio antennas (single channel)	0.5 m outside structure	—	—	—	—	—	40–50
	Ambient level	—	—	20–30	15–25	—	—
	Edge of structure	—	—	50	—	—	—
	1 m outside structure	—	—	95	—	—	—
Platform between local FM radio antennas	Near feeders	—	—	—	150	—	—
	Ambient level	—	—	—	—	30–40	—
	Near steelwork	—	—	—	—	100	—
Platform on outside of structure beneath local FM radio antennas	Near splitters	—	—	—	—	200	—
	Ambient level	—	—	—	—	10–50	—
	Near steelwork	—	—	—	—	80	—

above the instruments upper threshold were assigned the upper threshold value (i.e. 120% of ICNIRP). The bottom of each line indicates the rms if it is assumed that all measurements below the threshold of detection were zero.

Work activity questionnaires

Data from a total of 1253 questionnaires completed by 213 individuals were collated. Job titles were

placed into one of five categories, defined in conjunction with the participating companies and reflective of their core role. Riggers working for broadcasters spend some four times longer working in exposed areas than their counterparts working for mobile phone operators. Those working in Antenna Support spend similar time working in exposed areas across both sectors of the industry. The data for both operators and broadcasters are summarised in Table 5.

Exposure versus job group

In combining the findings from the work activity questionnaires with the exposure data stratified by type of site, it is clear that riggers working in broadcast companies are more likely to experience higher RF exposure than other groups of workers. In addition, they also spend more time in exposed locations. By comparison workers employed by operators attending singly located antennas experience far lower levels of exposure than their counterparts in the broadcast industry, levels that are typically below the detection level of the monitors used in this study.

DISCUSSION

Using data aggregated from personal monitor measurements of employees within broadcasters and mobile network operators, an estimate of exposure by site for both groups was produced. Linking personal exposure measurements at each site to work activity diaries from staff at each company shows that riggers in broadcast companies receive the highest exposure and for the longest duration. The least exposed are those workers whose sole exposure is from working at ground level or otherwise visiting singly located mobile phone antennas.

Strengths and limitations

The support of key staff at each company meant the research team were able to gather comprehensive and

representative data on work patterns and personal exposure. This has allowed for the first time to begin the process of providing meaningful estimates of exposure by job group across sector and site.

The sensitivity of the Wandel & Goltermann monitor used for the majority of the study was limited by its internal noise, which can reach as high as 25% of the reference levels and led to an overestimation of exposure at low-powered sites. Personal monitoring technology has improved in its sensitivity over the period since this study was done²⁰. The monitor produces a shaped response designed to offer practical assistance to the wearer of their compliance with ICNIRP guidelines and does not allow further interrogation of the data. However some context for the environments has been provided, it was investigated through a series of spot measurements using broadband survey metres.

The numbers of completed work activity questionnaires varied between organisations. Social desirability reporting can introduce bias in completing questionnaires²¹, though there is no reason to believe that employees within one industry would be more prone to this than another and so relative differences would remain.

Specific findings

Previous measurements in telecom and broadcasting have indicated that routine exposure is generally low¹⁶ and though some spot measurements around




Figure 1. Root mean square and maximum electric field exposure indices at various categories of site. The maximum exposures are presented as a cross. The broken line indicates the upper limit of detection of the ESM-20.

Table 5. Summary of work activity questionnaires by job category and sector.

	Antenna support	General maintenance worker	Occasional climber	Rigger	Satellite support
<i>Operators</i>					
Number of individuals	46	3	5	5	
Number of questionnaires	222	15	25	44	
Average working hours per shift	8.2	7.5	8.7	8.7	
Average working hours in exposed areas per shift	0.5	0.0	0.1	0.3	
<i>Broadcasters</i>					
Number of individuals	10	4	10	61	5
Number of questionnaires	62	171	126	563	25
Average working hours	7.6	7.8	8.0	8.8	9.3
Average working hours in exposed areas	0.6	0.3	0.0	1.2	0.0

the VHF antennas did exceed 100 V m^{-1} these were made at the rear of antennas close to steelwork where re-radiation can occur or at splitters where leakage was acknowledged. All of these measurements were made in the highly localised conditions of near-field radiation and are not necessarily indicative of whole-body exposure. However, evidence of occupational exposure is scant and there has been only one study that tried to explore differences in exposures between groups of workers in these industries¹⁵. Our work provides compelling evidence that in the UK those working on broadcast towers are more exposed to higher electric fields despite the strictly controlled working environment. This may be due to the busy nature of many of the taller structures where broadcast antennas are sited and not necessarily a result of the more powerful antennas, which would typically be powered down or turned off prior to the structure being accessed.

While the relationship between occupations involving exposure to RF and a number of health outcomes (especially cancer and reproductive outcomes) has been the subject of a number of epidemiological studies, the lack of accurate exposure data is a major deficiency²². Traditionally occupational exposures have been assessed through the measurement of electric and magnetic field strength using portable hazard survey instrumentation^{23–25}. However, the worker's exposure depends on the source's power, modulation scheme and field pattern, as well as the worker's behaviour and adherence to proper safety practice¹⁶.

More recently, personal monitors have been recommended as the best means of assessing individual exposures of those working in the telecommunication and broadcasting industries^{26, 27}. Their convenience means that they are suited for use in future epidemiological studies^{14, 16}.

There have been several calls for the use of personal monitors in assessing occupational exposure^{14, 28},

despite the fact that electric and magnetic fields can be perturbed by the presence of the human body^{28–31}. The evidence presented here appears to demonstrate that they are able to provide robust measures of personal exposure. Since this work was conducted a number of more sophisticated monitors²⁰ more sensitive and able to record data for a longer period of time have emerged. In addition, statistical analyses^{32, 33} have emerged that can account for missing data points that these were experienced.

Also relevant to the assessment of occupational exposure to RF is the prevalence of the sophisticated 'smartphone' technology, which has already been used to successfully measure personal exposure in other areas³⁴. The comparatively advanced computing capabilities this technology offers including global positioning services and barometry, allowing accurate measurements of an individual's height above ground³⁵. Utilising this functionality means that data on antennas at a given site could be combined with the height of the individual during specific periods of time to annotate personal measurements and produce a more precise exposure metric.

Future research

In Europe, the need for the identification of source-based measurement data and the importance of historical exposure has been recognised³⁶. In the UK, the National Register of RF Workers will use such data to inform exposure categories in future analyses³⁷. Meanwhile across the developing world, where the reliance on RF-based industries continues to grow³⁸, the number of employees occupationally exposed to RF continues to increase. This work demonstrates that it is possible to produce high-quality exposure estimates based on a combination of data from monitors and questionnaires that can be used to inform future epidemiological analyses.

REFERENCES

1. Grajewski, B. *et al.* Semen quality and hormone levels among radiofrequency heater operators. *J. Occup. Environ. Med.* **42**(1), 993–1005 (2000).
2. Christensen, H. C., Schuz, J., Kosteljanetz, M., Poulsen, H. S., Thomsen, J. and Johansen, C. *Cellular telephone use and risk of acoustic neuroma.* *Am. J. Epidemiol.* **159**(3), 277–283 (2004).
3. INTERPHONE Study Group. *Brain tumour risk in relation to mobile telephone use: results of the INTERPHONE international case-control study.* *Int. J. Epidemiol.* **39**, 675–694 (2010).
4. Hardell, L., Mild, K. H., Carlberg, M. and Hallquist, A. *Cellular and cordless telephone use and the association with brain tumors in different age groups.* *Arch. Environ. Health* **59**, 132–137 (2004).
5. Rolland, M., Le Moal, J.I., Wagner, V., Royere, D. and DeMouzon, J. *Decline in semen concentration and morphology in a sample of 26 609 men close to general population between 1989 and 2005 in France.* *Hum. Reprod.* **28**, 462–470 (2013).
6. Barth, A., Winker, R., Ponocny-Seliger, E., Mayhofer, W., Ponocny, I., Sauter, C. and Vana, N. *A meta-analysis for neurobehavioural effects due to electromagnetic field exposure emitted by GSM mobile phones.* *Occup. Environ. Med.* **65**, 342–346 (2008).
7. Independent Expert Group on Mobile Phones. *Mobile phones and health. Stewart Report.* IEGMP, (2010).
8. Directive 2013/35/EU of the European Parliament and of the Council of 26 June 2013 on the minimum health and safety requirements regarding the exposure of workers to the risks arising from physical agents (electromagnetic fields) (20th individual Directive within the meaning of Article 16(1) of Directive 89/391/EEC) and repealing Directive 2004/40/EC. (2013).
9. Vijayalaxmi and Scarfi, M. R. *International and national expert group evaluations: biological/health effects and radiofrequency fields.* *Int. J. Environ. Res. Public Health* **11**, 9376–9408 (2014).
10. Eurobarometer. 73.3 special eurobarometer 347 electromagnetic fields. http://ec.europa.eu/public_opinion/archives/ebs/ebs_347_en.pdf (last accessed on June 2016) (2010).
11. International Agency for Research on Cancer. Non-ionizing radiation, part 2: radiofrequency electromagnetic fields. IARC Monographs Volume 102. <https://monographs.iarc.fr/ENG/Monographs/vol102/mono102.pdf> (last accessed on June 2016) (2013).
12. Wyde, M. *et al.* Report of partial findings from the National Toxicology Program carcinogenesis studies of cell phone radiofrequency radiation in hsd: Sprague Dawley SD rats (whole body exposure). *bioRxiv*. (2016). Published online first: 26 May 2016. doi:10.1101/055699
13. World Health Organization. WHO research agenda for radiofrequency fields. http://whqlibdoc.who.int/publications/2010/9789241599948_eng.pdf (last accessed on June 2016) (2010).
14. Cooper, T. G., Allen, S. G., Blackwell, R. P., Litchfield, I., Mann, S. M., Pope, J. M. and van Tongeren, M. J. A. *Assessment of occupational exposure to radiofrequency fields and radiation.* *Radiat. Prot. Dosim.* **111**(2), 191–203 (2004).
15. Chauvin, S., Gibergues, M. L., Wuthrich, G., Picard, D., Desreumaux, J. P. and Bouillet, J. C. *Occupational exposure to ambient electromagnetic fields of technical operational personnel working for a mobile telephone operator.* *Radiat. Prot. Dosim.* **136**, 185–195 (2009).
16. Hareuveny, R., Kavet, R., Shachar, A., Margalio, M. and Kheifets, L. *Occupational exposures to radiofrequency fields: results of an Israeli national survey.* *J. Radiol. Prot.* **35**, 429–445 (2015).
17. International Commission on Non-Ionizing Radiation Protection. *Guidelines for limiting exposure to time-varying electric, magnetic and electromagnetic fields (up to 300 GHz).* *Health Phys.* **74**, 494–522 (1998).
18. Narda. Nardalert XT personal monitor datasheet. http://www.narda-sts.us/pdf_files/DataSheets/Nardalert_DataSheet.pdf (last accessed June 2016).
19. Greene, K. D. and Newman, M. C. Uncensor 4.0 software. <http://www.osti.gov/scitech/biblio/212077> (1995).
20. Thielens, A. *et al.* *Personal distributed exposimeter for radio frequency exposure assessment in real environments.* *Bioelectromagnetics* **34**, 563–567 (2013).
21. van de Mortel, T. F. *Faking it: social desirability response bias in self-report research.* *Aust. J. Adv. Nurs.* **25**(4), 40–48 (2008).
22. Ahlbom, A., Green, A., Kheifets, L., Savitz, D. and Swerdlow, A. *Epidemiology of health effects of radiofrequency exposure.* *Environ. Health Perspect.* **112**, 1741–1754 (2004).
23. Mild, K. H. *Radiofrequency electromagnetic fields in Swedish radio stations and tall FM/TV towers.* *Bioelectromagnetics* **2**, 61–69 (1981).
24. National Council on Radiation Protection and Measurements. *A practical guide to the determination of human exposure to radiofrequency fields.* NCRP Report 119 (Bethesda, MD: NCRP) (1993).
25. Floderus, B., Stenlund, C. and Carlgren, F. *Occupational exposures to high frequency electromagnetic fields in the intermediate range (>300 Hz–10 MHz).* *Bioelectromagnetics* **23**, 568–577 (2002).
26. Alanko, T. and Hietanen, M. *Occupational exposure to radiofrequency fields in antenna towers.* *Radiat. Prot. Dosim.* **123**(4), 537–539 (2007).
27. Mann, S. *Assessing personal exposures to environmental radiofrequency electromagnetic fields.* *C. R. Phys.* **11**(9–10), 541–555 (2010).
28. Blas, J., Lago, F. A., Fernández, P., Lorenzo, R. M. and Abril, E. J. *Potential exposure assessment errors associated with body-worn RF dosimeters.* *Bioelectromagnetics* **28**(7), 573–576 (2007).
29. Iskra, S., McKenzie, R. and Cosic, I. *Factors influencing uncertainty in measurement of electric fields close to the body in personal RF dosimetry.* *Radiat. Prot. Dosim.* **140**(1), 25–33 (2010).
30. Bolte, J. F. B., van der Zande, G. and Kamer, J. *Calibration and uncertainties in personal exposure measurements of radiofrequency electromagnetic fields.* *Bioelectromagnetics* **32**(8), 652–663 (2011).
31. Rodriguez, B., Blas, J., Lorenzo, R. M., Fernández, P. and Abril, E. J. *Statistical perturbations in personal exposure meters caused by the human body in dynamic outdoor environments.* *Bioelectromagnetics* **32**(3), 209–217 (2011).
32. Röösl, M., Frei, P., Mohler, E., Braun-Fahrlander, C., Bürgi, A., Fröhlich, J., Neubauer, G., Theis, G. and

- Egger, M. *Statistical analysis of personal radiofrequency electromagnetic field measurements with nondetects*. *Bioelectromagnetics* **29**, 471–478 (2008).
33. Iskra, S., McKenzie, R. and Cosic, I. *Monte Carlo simulations of the electric field close to the body in realistic environments for application in personal radiofrequency dosimetry*. *Radiat. Prot. Dosim.* **147**(4), 517–527 (2011).
 34. Breen, M. S. *et al.* *GPS-based microenvironment tracker (MicroTrac) model to estimate time-location of individuals for air pollution exposure assessments: model evaluation in central North Carolina*. *J. Expo. Sci. Environ. Epidemiol.* **24**, 412–420 (2014).
 35. del Rosario, M. B., Redmond, S. J. and Lovell, N. H. *Tracking the evolution of smartphone sensing for monitoring human movement*. *Sensors* **15**, 18901–18933 (2015).
 36. Vila, J. *et al.* *A source-based measurement database for occupational exposure assessment of electromagnetic fields in the INTEROCC study: a literature review approach*. *Ann. Occup. Hyg.* **60**(2), 184–204 (2016).
 37. Litchfield, I. *National register of radiofrequency workers: exploring health effects of occupational radiofrequency radiation exposure*. *J. Environ. Occup. Sci.* **3**(4), 190–192 (2014).
 38. Azah, C. K., Amoako, J. K. and Fletcher, J. J. *Levels of electric field strength within the immediate vicinity of FM radio stations in Accra, Ghana*. *Radiat. Prot. Dosim.* **156**(4), 395–400 (2013).