

Smart sensors to detect movements of cobbles and large woody debris dams. Insights from lab experiments.

Sgarabotto, Alessandro; Manzella, Irene; Raby, Alison; Roskilly, Kyle; Egedusevic, Martina; Panici, Diego; Clark, Miles; Boulton, Sarah J.; Franco, Aldina M. A.; Bennett, Georgina L.; Luo, Chunbo

DOI:

[10.5194/egusphere-egu23-16276](https://doi.org/10.5194/egusphere-egu23-16276)

License:

Creative Commons: Attribution (CC BY)

Document Version

Publisher's PDF, also known as Version of record

Citation for published version (Harvard):

Sgarabotto, A, Manzella, I, Raby, A, Roskilly, K, Egedusevic, M, Panici, D, Clark, M, Boulton, SJ, Franco, AMA, Bennett, GL & Luo, C 2023, 'Smart sensors to detect movements of cobbles and large woody debris dams. Insights from lab experiments.', EGU General Assembly 2023, Vienna, Austria, 24/04/23 - 28/04/23. <https://doi.org/10.5194/egusphere-egu23-16276>

[Link to publication on Research at Birmingham portal](#)

General rights

Unless a licence is specified above, all rights (including copyright and moral rights) in this document are retained by the authors and/or the copyright holders. The express permission of the copyright holder must be obtained for any use of this material other than for purposes permitted by law.

- Users may freely distribute the URL that is used to identify this publication.
- Users may download and/or print one copy of the publication from the University of Birmingham research portal for the purpose of private study or non-commercial research.
- User may use extracts from the document in line with the concept of 'fair dealing' under the Copyright, Designs and Patents Act 1988 (?)
- Users may not further distribute the material nor use it for the purposes of commercial gain.

Where a licence is displayed above, please note the terms and conditions of the licence govern your use of this document.

When citing, please reference the published version.

Take down policy

While the University of Birmingham exercises care and attention in making items available there are rare occasions when an item has been uploaded in error or has been deemed to be commercially or otherwise sensitive.

If you believe that this is the case for this document, please contact UBIRA@lists.bham.ac.uk providing details and we will remove access to the work immediately and investigate.



Smart sensors to detect movements of cobbles and large woody debris dams. Insights from lab experiments.

Alessandro Sgarabotto¹, Irene Manzella^{1,2}, Alison Raby³, Kyle Roskilly⁴, Martina Egedusevic⁵, Diego Panici⁶, Miles Clark⁷, Sarah J. Boulton¹, Aldina M. A. Franco⁷, Georgina L. Bennett⁵, and Chunbo Luo⁸

¹School of Geography, Earth and Environmental Sciences, University of Plymouth, Plymouth, UK

²Faculty of Geo-Information Science and Earth Observation, University of Twente, Enschede, NL

³School of Engineering, Computing and Mathematics, University of Plymouth, Plymouth, UK

⁴Environment and Sustainability Institute, University of Exeter, Penryn, UK

⁵College of Life and Environmental Sciences, University of Exeter, Exeter, UK

⁶Department of Engineering, University of Exeter, Exeter, UK

⁷School of Environmental Sciences, University of East Anglia, Norwich, UK

⁸Department of Computer Science, University of Exeter, Exeter, UK

An increase in population pressure and severe storms under climate change have greatly impacted landslide and flood hazards globally. At the same time, recent advances in Wireless Sensor Network (WSN) and Internet of Things (IoT) technologies, microelectronics and machine learning offer new opportunities to effectively monitor stability of boulder and woody debris on landslides and in flood-prone rivers. In this framework, smart sensors embedded in elements within the landslide body and the river catchment can be potentially used for monitoring purposes and for developing early warning systems. This is because they are small, light-weight, and able to collect different environmental data with low battery consumption and communicate to a server through a wireless connection. However, their reliability still needs to be evaluated. As data from field sites could be fragmented, laboratory experiments are essential to validate sensor data and see their potential in a controlled environment. In the present study, dedicated laboratory experiments were designed to assess the ability of a tag equipped with an accelerometer, a gyroscope, and a magnetometer to detect movements in two different settings. In the first experimental campaign, the tag was installed inside a cobble of 10.0 cm diameter within a borehole of 4.0 cm diameter. The experiments consisted in letting the cobble fall on an experimental table composed of an inclined plane of 1.5 m, followed by a horizontal one of 2.0 m. The inclined plane can be tilted at different angles (18° - 55°) and different types of movement have been generated by letting the cobble roll, bounce, or slide. Sliding was generated by embedding the cobble within a layer of sand. The position of the cobble travelling down the slope was derived from camera videos by a tracking algorithm developed within the study. In the second experimental campaign, a simplified analogue model of a woody debris dam was built from a single hollowed dowel with a length of 40 cm and a diameter of 3.8 cm. The sensor tag is installed in the woody dowel within a 2.5 cm longitudinal borehole. Two metal rigs are mounted at both

sides of the woody dowel to allow different modes of movement. Specifically, the woody dowel is allowed to move either horizontally or vertically within a range of 20-30 mm, whereas it is always free to complete full rotations. The woody dowel is mounted on a frame within a 20 m long and 0.6 m wide flume. In these two experimental settings, combining data from the accelerometer, gyroscope and magnetometer it was possible to detect movements and differentiate between different type of motions both in a woody dowel and in the cobble under different initial conditions. Data were analysed to understand which type of information could be retrieved. This gives important insights for the assessment of the feasibility and effectiveness of the use of smart sensors in the detection of movements in woody logs within dams and boulders embedded in landslides, thus providing indications for the development of early warning systems using this innovative technology.